

Supplier	TOSHIBA CARRIER CORPORATION	
Indoor unit	RAS-B10J2KVG-E	
Indoor unit	RAS-B10J2KVG-E	
Outdoor unit	RAS-2M14U2AVG-E	

Sound power level

indoor unit (cooling)	dB	54
outdoor unit (cooling)	dB	58
indoor unit (heating)	dB	54
outdoor unit (heating)	dB	59

Refrigerant

Type	R32	
Global Warming Potential	kgCO ₂ eq	675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

Energy efficiency class	A++	
Design load (Pdesignc)	kW	4,00
Seasonal efficiency (SEER)	6,54	
Seasonal electricity consumption (QCE)	kWh/annum	214

Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A+	—	—
Design load (Pdesignh)	kW	3,10	—	—
Seasonal efficiency (SCOP)		4,54	—	—
Seasonal electricity consumption (QHE)	kWh/annum	956	—	—
Back up heating capacity	kW	0,73		
Declared capacity for heating, at indoor temperature 20°C and outdoor temperature Tj.				
Tj= -7°C (Pdh)	kW	2,74	-	—
Tj= 2°C (Pdh)	kW	1,67	—	—
Tj= 7°C (Pdh)	kW	1,95	—	—
Tj= 12°C (Pdh)	kW	2,28	—	—
Tj=bivalent temperature (Pdh)	kW	2,74	—	—
Tj=operation limit (Pdh)	kW	1,14	—	—
Tj= -15°C (Pdh)	kW	-	-	—